



3/4 SHOCK MOUNTS (4 PLS)
(INCLUDED WITH LIGHT CURTAIN,
NOT INCLUDED IN HARDWARE KIT)

ADJ. 'c' DIST.
MAX. = 33 1/4"
MIN. = 20 1/4"

ADJ. 'd' DIST.
MAX. = 40 1/2"
MIN. = 24 1/2"

* NOTE:
MINIMUM 'c' DISTANCE CAN BE 4" IF BASE AND
ELBOW ARE CUT OFF. DO NOT CUT BASE
AND ELBOW TO LESS THAN 4" EACH.

** NOTE:
MINIMUM 'd' DISTANCE CAN BE 9" IF PIVOT IS CUT
TO 9" AND T-CONNECTOR IS CUT TO 4". DO NOT
CUT PIVOT OR T-CONNECTOR TO LESS THAN 9"
AND 4" RESPECTIVELY.

ADD TO 'd' DIST. THE
DISTANCE FROM VERT.
SUPPORT TO SENSING FIELD:
2.0"

1 ASSEMBLY (6 PCS) FOR EACH TRANSMITTER OR RECEIVER

ASSEMBLY P/N	BLACK MAX UNIT	VERT. SUPPORT
900383	18", 24"	34"
900384	30", 36"	48"
900385	42", 48"	60"

FINISH: CARBIDE BLACK

ALL NUTS, BOLTS, WASHERS, IN HARDWARE KIT
LINK P/N: 106536 (66 PCS)

DESCRIPTION	QTY	LINK P/N:
SHOULDER BOLTS (3/8-16 X 1/2 X 2 1/4)	2	101663
WASHERS (1/2 FLAT)	2	105191
BOLTS (HEX 3/8-16 X 2 1/2)	14	106135
WASHERS (3/8 FLAT)	30	103311
NUTS (NYLOCK 3/8-16)	16	102249
305 MTG BRACKET	2	105409

WARNING!!

The Link Lite Black Max must be installed so that the distance between its sensing field and the nearest point of operation hazard is greater than or equal to the minimum safety distance which must be calculated by a formula specified by OSHA and ANSI. See latest editions OSHA 1910.217, ANSI B11.1 and B11.19.

VERT. SUPPORT (1 3/4" TUBE)	LINK P/N
34"	106246
48"	106247
60"	106248

NO	DESCRIPTION	DATE	BY
1	REVISED PART: 106523	1-23-98	JCN

REVISIONS

The drawing link/ or modified information to the property of LINK ELECTRIC & SAFETY CONTROL CO. in confidence and is not to be reproduced for others without LINK's prior written consent.

LINK SYSTEMS
LINK ELECTRIC & SAFETY CONTROL CO.
444 McHenry Dr. • Nashville, TN, 37211

LINK LITE BLACK MAX MOUNTING
SWINGARM BRACKET
DRAWING P/N: 106615

SCALE	DATE	CODE IDENT NO
1=3	5-7-96	305
DWN BY	CHK BY	DRAWING NUMBER
JCN		C-305-1124